

T2380



Tally

“Unsurpassed excellence”. That defines the rugged high powered T2380 Printer. Built to leave a lasting impression on your productivity, this high speed workhorse exemplifies what rugged durability is all about. With its advanced 24 pin print head, the T2380 is engineered to perform at a blistering pace even in the harshest of operating environments. You’re assured of top-shelf performance, crisp, clear and reliable print quality and a machine you can count on when your performance is what counts.

Low running costs and durability in the harshest of print environments make these products excellent value of money.

Highlights at a glance:

- Full range of automatic features to minimize user intervention
- Ideal for “On-Demand” and “Batch” applications with zero tear for no wasted forms
- Straight through paper path for easy forms loading
- Parallel and Ethernet (10/100 Base T) standard
- Optional Interfaces: RS-232 Serial; Coax/Twinax; Ethernet IPDS
- Compatible with a wide range of operating systems including Windows, Unix, DOS, SAP R3 and legacy systems

These products are well matched to Microsoft Windows applications, and highly compatible with other Host operating environments including Legacy systems.

Fully automated operations, coupled with the straight through paper path, allows ease of use and virtually eliminates errors caused by user intervention.

Intelligent Mail Barcode - make sure your Printer has this feature

The US Postal Service new bar code standard will require this capability to take advantage of the best rates available.

Intelligent Mail Barcode sample



SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS

CONNECTIVITY

CONSUMABLES

Available Configuration:

- **T2380** Standard Product
- **T2380 2T** with additional rear tractor

T2380

Print Speed	1,000 cps (Fastest Draft); 800 cps (Draft), 22 cps (NLQ) at 10 cpi
Resolution	Up to 360 x 360 dpi
Throughput (ECMA 132)	680 pages per hour
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Printhead Life	750 million strokes per pin
Standard Memory	128 kB
Standard Connectivity	Parallel (Bi-Directional IEEE 1284) and Ethernet (10/100 Base T)
Optional Connectivity	RS_232 Serial, Ethernet with SCS or IPDS, Coax/Twinax and SCS or IPDS
Standard Emulation	Epson LQ (ESC P/2), IBM Proprinter XL24e, MTPL + Barcodes, Genicom ANSI
Optional Emulation	PCL 3 (Rugged Writer), IGP/PGL, Code V, MT660, Printronix P6000, HP2564c
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and scaleable Large Character Printing
Consumables	Ribbon: 20 million (standard)
Standard Paper Handling	Push Tractor for continuous paper with straight paper path, Tear off and Park position.
Optional Paper Handling	Additional Push Tractor (front), Automatic Cutting Device
Number of Copies	Push Tractor (Front) 1 original + 5 copies Push Tractor (Rear) 1 original + 3 copies (2T version)
Paper Type	Continuous Forms, Multi-Part Forms (.025" thick max.)
Paper Weight	60 - 120 g/m ²
Paper Size	Width: 3" to 16.5"; Length: 3" to 22"
Physical Weight	24.5 lbs.
Physical Size	24.5" x 17" x 11" (W x D x H)
Acoustic	59 db(A)
Power Voltage	120 or 240 (V) (auto-switching)
Power Consumption	70 (W) Printing; 18 (W) Power-Save
Temperature	+ 50 to +95 F; 20% to 80% humidity (not condensing)
Workload	50,000 pages per month
MTBF	12,500 hours
Warranty	90 days On-Site Warranty
Drivers	Windows 2000/XP/Vista/7/8/10 and Server 2003/2008/2012; SAP
Note	For OCR applications, it is recommended that your Reader calibrated. Paper is a highly variable medium and should be tested prior to purchase.

DASCOM Americas Corporation

34 Lakeview Court
Verona, Virginia 24482
Tel: (877) 434-1377
www.dascomamericas.com

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 