

## Tally DASCOM LA2810



# Tally

The LA2810 printer is designed for fast, efficient performance under the most rigorous conditions in challenging environments. Built to perform, the LA2810 gives users exceptional print speeds, throughput, and workload capability for heavy operation in demanding environments.

An excellent value, the LA2810 offers low operation costs and is well matched to DEC environments.

User intervention is minimized, and menu settings can even be saved via the USB host.

### Highlights at a glance:

- Print up to 960 characters per second at 12 CPI
- Rated workload 50,000 printed pages per month
- Long-life print head rated at 750 million characters
- Ethernet interface with IPv4 and IPv6 support
- Variety of Connectivity Options
- Print up to 7 copies (original + 6)
- Metal tear-off edge for no wasted forms
- Low decibel quiet operation
- Industrial design for demanding environments

A backlit display means all information can be read easily.

The browser-based Tally DASCOM Web Panel is then available for network management.

Equipped with an Ethernet interface, with both IPv4 and IPv6 support, and a USB interface as standard, the printer can also be upgraded with serial/parallel or a coax interface thus making it flexible and easy to integrate into many systems.



### Common Applications:

- Warehouse environments
- Manufacturing
- Trucking & Logistics
- Retail
- Other industrial environments

SERIAL MATRIX PRINTERS

CARD PRINTERS

THERMAL PRINTERS

POS PRINTERS

CONNECTIVITY




CONSUMABLES

SERVICE

# Tally DASCOM LA2810

<b>Print Speed</b>	960 cps (Fastest Draft); 1000 cps (Draft), 333 cps (NLQ) at 12 cpi
<b>Resolution</b>	Up to 360 x 360 dpi (ESC/P Emulation only)
<b>Throughput</b>	640 pages per hour (ECMA 132 @ 10cpi)
<b>Character Density</b>	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Print Head Life</b>	750 million characters
<b>Standard Memory</b>	256 Kb
<b>Standard Connectivity</b>	USB 2.0 (Full Speed) and Ethernet 10/100 Base T with Ipv6 support. USB host
<b>Optional Connectivity</b>	Parallel IEEE1285 and RS-232 Serial combo interface with MMJ Adapter, Ethernet Multi-protocol, Ethernet with SCS or IPDS, Coax with SCS or IPDS support
<b>Standard Emulations</b>	DEC PPL2, IBM Proprinter XL24e, EPSON LQ ESC P/2
<b>Fonts</b>	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 23 Barcodes and scale-able Large Character Printing
<b>Consumables</b>	Ribbon: 20 million characters (draft)
<b>Administration</b>	Internal Web Page, System settings/firmware upload via USB host interface, Backlit Panel
<b>Standard Paper Handling</b>	Push Tractor for straight paper path using continuous paper, Tear off and Park position, Dual friction for better paper handling
<b>Optional Paper Handling</b>	Additional Push Tractor (front)
<b>Number of Copies</b>	Push Tractor (Front) 1 original + 5 copies
<b>Paper Type</b>	Continuous Forms, Multi-Part Forms (.025" thick max.)
<b>Paper Weight</b>	60 – 120 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 3" to 16.5" (76 mm – 419 mm), Length: 3" to 22" (76 mm – 560 mm)
<b>Physical Size (W x D x H)</b>	24.5" x 17" x 11" (624 x 432 x 280 mm)
<b>Physical Weight</b>	42 lbs (Approximately 19 kg)
<b>Acoustic</b>	54 dB(A)
<b>Power Voltage</b>	120 V or 230 V (auto-switching)
<b>Power Consumption</b>	75 Watt while Printing; 2 Watts power save
<b>Workload</b>	Up to 50,000 pages per month
<b>Drivers</b>	Windows 8/10 (32 and 64 bits) and Server 2012/2016; SAP
<b>Reliability MTBF</b>	20,000 hours
<b>Temperature</b>	50 °F– 95 °F(+10 °C to +35 °C)
<b>Humidity</b>	15% to 75% RH (not condensing)
<b>Warranty</b>	90 days on-site warranty
<b>Options</b>	2nd tractor, Print stand

DASCOM Americas  
 34 Lakeview Court  
 Verona, Virginia, 24482 USA.  
 Tel: +1 (877) 434-1377  
[www.dascomamericas.com](http://www.dascomamericas.com)  
[info.us@dascom.com](mailto:info.us@dascom.com)

THERMAL PRINTERS   
 CARD PRINTERS   
 MATRIX PRINTERS   
 POS PRINTERS 