

ML3410 Specifications

OKI
Open up your dreams



The heavy-duty, high speed 9-pin printer for large-volume forms printing

Powerful and reliable

The ML3410 is a powerful, dependable, 9-pin dot matrix printer designed to handle the most data-intensive applications at very high speeds.

With impressive copy capabilities the ML3410 can produce up to eight multi-part copies at any one time, whilst maintaining clarity and providing extraordinary print quality on any surface.

Perfect for heavy duty print runs

With the flexibility of three paper paths, the ML3410 is ideally suited to businesses requiring heavy duty throughput on a variety of paper stock.

With parallel and serial interfaces as standard the ML3410 is perfect for networked / shared environments including purchasing, distribution, accounts, finance and IT departments.

OKI's commitment to customers

The OKI brand is one of proven reliability and value. We provide printers that increase our customers' long-term business performance without impacting their budget.

With almost half a century of experience in the impact printer industry, with OKI you are guaranteed a best-in-class, low cost, reliable and easy to use printer.

Highlights:

- 136/272 column dot matrix printers
- Zero tear with auto from advance
- OKI's unique, high durability 9-pin printhead
- Multi-part continuous forms handling (original + 5 copies)
- Up to 550 characters per second (cps) print speed

Variant available:
ML3410



ML3410 - Dot Matrix Printer

PRINTER	
Number of pins	9
Columns	136 (10cpi); 272 (maximum in compression mode)
Character pitch	10/12/15/17.1/20 pitch and proportional
Graphics resolution	Up to 240 x 216dpi
Print speed	High Speed Draft: 550cps (10/12cpi); Utility: 417cps (10/12cpi); Near Letter Quality: 104cps (10/12cpi)

INTERFACE AND EMULATIONS	
Interfaces	Centronics parallel interface, Serial RS 232C, Dual interface
Emulations	Epson FX, IBM ProPrinter XL
Optional emulations	Microline, Pacemark
Typeface & font	HSD, Utility, NLQ-Courier, NLQ-Gothic, Barcodes, OCR-B
Typestyle	Emphasised, Enhanced, Double Width, Double Height, Italics, Superscript, Subscript, Underline, Overscore

PAPER HANDLING	
Continuous paper	76.2 - 406.4mm
Continuous envelopes	239 x 102mm
First printable line (from top of page)	Continuous (multi-parts): 23.3mm; Cut sheet (single sheet): 25.4mm
Copy capability	Up to 1 original + 5 copies
Paper feeding	Autoload single sheet, Paper parking, Rear push tractors, Metal long-life tear-off bar
Optional paper feeding	Bottom push tractor

GENERAL FEATURES	
Input buffer	28Kbytes (reduced buffer)
Power supply	Single phase 220 to 240VAC, +/- 10%, frequency 50/60Hz, +/- 2%
Power consumption	Operating: 150W; Non-operating: 60W
Noise level	<58dB(A)
Dimensions (HxWxD)	203 x 570 x 482mm
Weight	18kg approx
Print Head life	200 million characters (average) in 10cpi Utility mode at normal 25% duty cycle, 35% page density
Reliability	MTBF: 8,000 hours (duty cycle 25%, page density 35%)
Product order numbers	YA4043-4210G402

ACCESSORIES (ORDER NUMBERS)	
Bottom push tractor	YA4043-4250G002

CONSUMABLES (ORDER NUMBER)	
Ribbon (7 million characters)	45445201

Consumables Information: Only use genuine OKI Original consumables to ensure the best quality and performance from your hardware. Non OKI Original products may damage your printer's performance and invalidate your warranty.

Okidata (Singapore) Pte Ltd
438A Alexandra Road
#02-11/12,
Lift Lobby 3,
Alexandra Technopark,
Singapore 119967
Tel: (65) 6221 3722
www.oki.com/sg/printing

Okidata (S) Pte Ltd
Malaysia Branch Office
Suite 21.03, 21st Floor,
Menara IGB, Mid Valley City,
59200 Kuala Lumpur, Malaysia
Tel: (03) 2287 1177
Tel: 1800 88 1177 (Toll Free)
Fax: (03) 2287 1166
www.oki.com/my/printing

Okidata Systems (Thailand) Ltd
1168/63 Lumpini Tower, 22nd Floor,
Rama IV Road., Tungmahamek, Sathorn
Bangkok 10120
Tel: (662) 679 9235
Fax: (662) 679 9243, 45
www.oki.com/th/printing

OKI